

imagePROGRAF TX-4100

AN ALL-ROUND, 44-INCH LARGE FORMAT PRINTER WITH ADVANCED PRODUCTIVITY AND RELIABLE QUALITY

High-capacity, multipurpose, large format inkjet printer for poster and CAD production, with enhanced usability and flexibility.



- **Fast printing**
Up to 3.2ppm for A1 CAD drawings by increased print speed and data processing
- **Improved security**
Advanced security features support the market requirements
- **Borderless capability**
Post-production cutting is minimised by free-size borderless printing
- **Unrivalled quality**
Innovative ink and printing processes deliver superb quality on all media types, even on uncoated paper
- **Expert media handling**
An intelligent detection system makes media setting simple and intuitive
- **Output durability**
Full pigment ink and a water resistant media option enhance the weather resistance of prints
- **High productivity**
Faster time to first print and uninterrupted printing from hot swap ink tank replacement

PRODUCT RANGE



imagePROGRAF TX-3100



imagePROGRAF TX-4100 MFP Z36



imagePROGRAF TX-3100 MFP Z36

Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF TX-4100

TECHNOLOGY			
Printer Type	5 Colour 44"	Borderless Printing Width (Roll Only)	[Recommended] 515mm(JIS B2), 594mm(ISO A1), 728mm(JIS B1), 841mm(ISO A0), 1030mm(JIS B0), 10", 14", 17", 24", 36", 42", 44" [Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 420mm(ISO A2), 6", 8", 12", 15", 16", 20", 22", 30", 34", 300mm, 500mm, 600mm, 800mm, 1000mm and custom roll width (152.4 - 1118mm) **"Printable" size is printed as micro margin technology, that means is not used with hole of platen.
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)	Maximum number of delivered prints	[Multi-position basket] Standard position: 1 sheet Flat position: A2 landscape, glossy paper 10 sheets, Coated paper 20 sheets, Plain paper 20 sheets (excludes strong curled condition) [Stacker] Basket position: 1 sheet (excludes curled condition) Folding position: A0/A1 portrait, CAD drawing, Plain paper 20 sheets, Uncoated paper 100 sheets (excludes curled condition) Stacking position: A1/A2 landscape, CAD drawing, Plain paper 100 sheets, Uncoated paper 100 sheets (excludes curled condition)
Print Resolution	2,400 x 1,200 dpi	DIMENSIONS AND WEIGHT	
Number of Nozzles	Total : 15,360 nozzles MBK : 5,120 nozzles BK, C, M, Y : 2,560 nozzles each	Physical Dimensions WxDxH (mm) and Weight (Kg)	1593 x 984 x 1168 mm (Basket Open) 1593 x 766 x 1168 mm (Basket Closed) 114 kg (including Roll Holder Set and Roll unit, excluding ink and print heads)
Line Accuracy	±0.1% or less	Packaged Dimensions WxDxH (mm) and Weight (Kg)	Printer (Main unit with pallet): 1820 x 915 x 1061 mm 161 kg Roll Unit: 1727 x 562 x 461 mm 30 kg
Nozzle Pitch	1,200 dpi x 2 includes Non-firing nozzle detection and compensation system	POWER AND OPERATING REQUIREMENTS	
Ink Droplet Size	5 pl per colour	Power Supply	AC 100-240V (50-60Hz)
Ink Capacity	Bundled Starter Ink: 330 ml (MBK, BK, C, M, Y) Sales Ink: 160ml/330ml/700ml	Power Consumption	Operation: 116 W or less Sleep mode: 2.0 W or less Default setting for the time to enter the Sleep mode: Approx. 5 Minutes Power off: 0.3 W or less
Ink Type	Pigment inks : 5 colour MBK/BK/C/M/Y	Operating Environment	Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)
OS Compatibility	Microsoft Windows 32 Bit: 7, 8.1, 10 64 Bit: Windows 7, Windows 8.1, Windows 10, Windows Server 2008R2, 2012, 2012R2, 2016, 2019 Apple Macintosh: macOS 10.12.6-macOS 10.15	Acoustic Noise (Power/Pressure)	Operation: 51 dB (A) (Plain paper, Standard mode, Line Drawing/Text mode) Standby: 35 dB (A) or less Operation: 6.9 Bels or less (Plain paper, Standard mode, Line Drawing/Text mode) (Measured on ISO 7779 standard)
Printer Languages	HP-GL/2, HP RTL, PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)	Regulations	Europe: CE mark, Other Countries : CB certification
Standard Interfaces	USB A Port: USB Memory Direct Print for JPEG/PDF files USB B Port: Built-in Hi-Speed USB Ethernet: 10/100/1000 base-T Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b *Please refer to user manual how to activate/deactivate the wireless LAN	Environment Certificates	TUV, CB
MEMORY		WHAT'S INCLUDED	
Standard memory	128GB (Physical memory 2GB) Expansion slot : No	What's in the Box?	Printer, 1 x Print Head, 1 x Roll holder (spool), 3" Paper Core Attachment, 1 Set of Starter Ink Tanks, Set Up Guide, Safety/Standard, Environment Leaflet User software CD-ROM (Windows), PosterArtist Lite CD-ROM EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet
Hard Drive	500GB (Encrypted)	Software Included	imagePROGRAF TX Printer Driver and PosterArtist Lite Other software available as Download from Web.
PRINTING SPEED		OPTIONS	
CAD Drawing:		Optional Items	2/3" Roll Holder: RH2-46 Roll Unit : RU-42 Stacker : SS-41
Plain Paper (A1)	0:18 (Fast Economy Mode), 3.2ppm	CONSUMABLES	
Plain Paper (A0)	0:34 (Fast Economy Mode) 0:37 (Fast) 1:04 (Standard)	User Replaceable Items	Ink Tank: PFI-110 (160ml), PFI-310 (330ml), PFI-710 (700ml) Print Head: PF-06 Cutter Blade: CT-07 Maintenance Cartridge: MC-30
Poster:		Notes & Recommendations	
Plain Paper (A0)	0:37 (Fast Economy Mode) 0:42 (Fast) 1:15 (Standard)	Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.	
Heavy coated Paper (A0)	1:38 (Fast) 2:33 (Standard)	Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.	
MEDIA HANDLING			
Media Feed and Output	Roll Paper : One Roll, Front-loading, Front Output Cut Sheet : Front-loading, Front Output (Manual feed using media locking lever)		
Media Width	Roll paper : 152.4mm - 1118mm Cut sheet : 152.4mm - 1118mm		
Media Thickness	Roll/Cut : 0.07mm - 0.8mm		
Minimum Printable Length	Roll paper : 101.6mm (Excluding Cloth, Canvas, Tracing Paper and Translucent Matte Film media. These media are 200mm.) Cut sheet : 203.2 mm		
Maximum Printable Length	Roll paper : 18 m (Varies according to the OS and application) Cut sheet : 1.6 m		
Maximum Media Roll Diameter	170 mm		
Media Core Size	Internal diameter of roll core: 2 1/3"		
Margins Recommended area	Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm		
Margins Printable area	Roll paper : Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless) : Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet : Top: 3 mm, Bottom: 20 mm, Side: 3 mm		
Media Feed Capacity	Roll Paper: Two rolls. Automatic switching is possible. Cut Sheet: 1 sheet		
Media Take-up roll unit	Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll		



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2021